

EVERSTEEL™

Designed to last



LABORATORY FAUCETS

STAINLESS STEEL FAUCETS

Eliminate the need for specialized non-metallic faucets and the tin-lining of traditional brass faucets

OUTLET STYLES

Serrated tip or aerators with 2.2 gpm or 0.5 gpm flow rates

MULTIPLE BODY STYLES AVAILABLE

Deck and Wall Mount
Single and Dual Temperature



STAINLESS STEEL 4-ARM HANDLES

Also available with 4" wrist action handles

STAINLESS STEEL QUARTER-TURN CERAMA CARTRIDGES

Check valves prevent water cross flow

FLEXIBLE STAINLESS SUPPLY HOSES



COMMERCIAL-DUTY CONSTRUCTION

Time-proven designs in premium stainless steel



LIMITED LIFETIME WARRANTY

Protects against defects in materials or workmanship



VERSATILE PERFORMANCE

20 - 125 psi [1.38 - 8.62 bar],
40°F - 14°F [4.44°C - 60°C]



STANDARDS COMPLIANCE

ASME A112.18.1/CSA B125.1, ADA
ANSI/ICC A117.1, A117.1, & NSF 372



HIGH EFFICIENCY MODELS AVAILABLE

Flow Rate: 0.5 GPM
[1.89 L/min] @ 60 psi [4.14 bar]